





07SPCS&FTRS

ENGINEERING	LX	EX	SC
Engine Type	In-Line 4-Cylinder	In-Line 4-Cylinder	In-Line 4-Cylinder
Engine Block/Cylinder Head	Aluminum-Alloy	Aluminum-Alloy	Aluminum-Alloy
Displacement (cc)	2354	2354	2354
Horsepower @ rpm (SAE net, Rev 8/04)*	166 @ 5800	166 @ 5800	166 @ 5800
Forque (lbft. @ rpm)*	161 @ 4000	161 @ 4000	161 @ 4000
Redline (rpm)	6500	6500	6500
Bore and Stroke <i>(mm)</i>	87 x 99	87 x 99	87 x 99
Compression Ratio	9.7:1	9.7:1	9.7:1
/alve Train	16-Valve DOHC i-VTEC®	16-Valve DOHC i-VTEC	16-Valve DOHC i-VTEC
Multi-Point Fuel Injection	•	•	•
Orive-by-Wire™ Throttle System	•	•	•
Real Time 4-Wheel Drive™	Available	Available	2WD
CARB Emissions Rating	LEV-2	LEV-2	LEV-2
Direct Ignition System with Immobilizer	•	•	•
00,000 Miles-or-More Tune-Up Interval†	•	•	•
TRANSMISSIONS			
5-Speed Manual Transmission			
Gear Ratios: 1st: 3.533, 2nd: 2.042, 3rd: 1.355, 4th: 1.028,			
5th: 0.825, Reverse: 3.583, Final Drive: 4.765			
5-Speed Automatic Transmission (Available)			
Gear Ratios: 1st: 2.786, 2nd: 1.614, 3rd: 1.082, 4th: 0.733,			
5th: 0.566, Reverse: 2.000, Final Drive: 4.500			
BODY/SUSPENSION/CHASSIS			
Jnit-Body Construction	•	•	•
Control-Link MacPherson Strut	•	•	
Front Suspension	<u> </u>	<u> </u>	•
Compact Double Wishbone Rear Suspension	•	•	•
Stabilizer Bar <i>(mm, front/rear)</i>	30.0/21.0	30.0/21.0	30.0/25.0
/ariable Power-Assisted	•		
Rack-and-Pinion Steering	<u> </u>	<u> </u>	<u> </u>
Steering Wheel Turns, Lock-to-Lock	3.26	3.26	2.98
Steering Ratio	16.2	16.2	15.3
Furning Diameter, Curb-to-Curb (ft.)	34.9	34.9	36.9
Power-Assisted Ventilated Front Disc/			
Solid Rear Disc Brakes (in.)	11 1/11 1		
	11.1/11.1	11.1/11.1	11.1/11.1
Nheels	11.1/11.1 16" with Full Covers	11.1/11.1 16" Alloy	11.1/11.1 18" Alloy

SAFETY	LX	EX	sc
3-Point Seat Belts at All Seating Positions	•	•	•
Front 3-Point Seat Belts w/Automatic Tensioning System	•	•	•
Dual-Stage, Dual-Threshold Front Airbags (SRS)	•	•	•
Front Side Airbags with Passenger-Side Occupant Position Detection System (OPDS)	•	•	•
Side Curtain Airbags with Rollover Sensor	•	•	•
Vehicle Stability Assist™ (VSA®) with Traction Control	•	•	•
Brake Assist	•	•	•
Anti-Lock Braking System (ABS)	•	•	•
Electronic Brake Distribution (EBD)	•	•	•
Side-Impact Door Beams	•	•	•
Tire Pressure Monitoring System (TPMS)	•	•	•
Lower Anchors and Tethers for Children (LATCH)	•	•	•
Immobilizer Theft-Deterrent System	•	•	•
EXTERIOR MEASUREMENTS			
Wheelbase (in.)	101.4	101.4	101.4
Length (in.)	169.3	170.3	170.8
Height (in.)	70.4	70.4	69.5
Width (in.)	71.5	71.5	71.5
Track (in., front/rear)	62.1/62.3	62.1/62.3	62.1/62.5
Ground Clearance (in., unladen)	6.9	6.9	6.2
Approach/Departure Angles (degrees)	25.8/27.8	25.8/27.8	19.5/21.2
Curb Weight (lbs., 2WD MT/2WD AT)	3433/3499	3456/3523	3529/3596

INITEDIOD MEASI IDEMENT

Towing Capacity⁶ (lbs.)

Curb Weight (lbs., 4WD MT/4WD AT)

Weight Distribution (% front/rear; 2WD)

Weight Distribution (% front/rear; 4WD)

INTERIOR MEASUREMENTS			
Headroom (in., front/rear; 2WD)	43.3/38.0	43.3/38.0	43.3/38.0
Headroom (in., front/rear; 4WD)	43.3/39.4	43.3/39.4	
Legroom (in., front/rear)	41.0/39.1	41.0/39.1	41.0/39.1
Shoulder Room (in., front/rear)	57.1/52.2	57.1/52.2	57.1/52.2
Hiproom (in., front/rear)	55.0/47.6	55.0/47.6	55.0/47.6
Cargo Volume ⁴ (cu. ft., behind 2nd row; 2WD/4WD)	25.1/26.0	25.1/26.0	25.1
Cargo Volume ⁴ (cu. ft., maximum; 2WD/4WD)	74.6/77.1	74.6/77.1	74.6
Passenger Volume (cu. ft., 2WD/4WD)	103.6/105.4	103.6/105.4	103.6
Seating Capacity	4	4	4

3567/3645

57/43

56/44

1500

3580/3661

57/43

1500

57/43

56/44

1500

^{*}Horsepower and torque calculations reflect SAE J1349 procedures revised August, 2004.

[†]Does not apply to fluid and filter changes. Exact mileage is determined by actual driving conditions. Please see your owner's manual for more details.





EPA MILEAGE ESTIMATES ⁵ /FUEL CAPACITY	LX	EX	SC
5-Speed Manual (<i>City/Highway; 2WD)</i>	21/25	21/25	21/25
5-Speed Automatic <i>(City/Highway; 2WD)</i>	22/27	22/27	22/27
5-Speed Manual <i>(City/Highway; 4WD)</i>	21/24	21/24	
5-Speed Automatic <i>(City/Highway; 4WD)</i>	21/26	21/26	
Crankcase (qt.)	5.6	5.6	5.6
Fuel <i>(gal.)</i>	15.9	15.9	15.9
Required Fuel	Regular Unleaded	Regular Unleaded	Regular Unleaded
EXTERIOR FEATURES			
Removable Skylight with Tilt Feature	4WD Models Only	4WD Models Only	
Side Cargo Doors	•	•	•
2-Speed/Intermittent Windshield Wipers	•	•	•
Remote Entry System	•	•	•
Power Side Mirrors	•	•	•
Composite Body Panels	Black	Body-Colored	Body-Colored
Body-Colored Door Handles		•	•
Body-Colored Bumpers			•
Body-Colored Side Sills and Roof Moldings			•
Rear Privacy Glass	•	•	•
Clamshell Tailgate	•	•	•
Alloy Wheels		•	•
Multi-Reflector Halogen Headlights	•	•	
Projector Beam Halogen Headlights			•
Chrome Exhaust Finisher		•	•
SEATING			
Driver's Seat with Manual Height Adjustment	•	•	•
Waterproof FXC ^{™3} (Fabric for Extreme	Front	Front and Rear	
Conditions) Seat Fabric	Tront	Tront and near	
Adjustable Head Restraints, Front and Rear	•	•	•
Driver- and Passenger-Side Armrests		•	Center Console
Removable, Flip-Up Rear Seats	•	•	•
Fold-Flat-Capable Seating	•	•	•
AUDIO SYSTEMS			
AM/FM/CD Audio System with 4 Speakers and Clock	•		
270-Watt AM/FM/CD Audio System with 7 Speakers, Including Subwoofer			
MP3/Windows Media® Audio¹ (WMA) Playback Capability		•	•
XM® Satellite Radio ²		•	•
MP3/Auxiliary Input Jack		•	•
mi of taxillary hipatoack			

COMFORT & CONVENIENCE	LX	EX	SC
Air Conditioning with Air-Filtration System	•	•	•
Power Front Windows with	•	•	•
Auto-Up/Down Driver's Window	<u>•</u>	<u>• </u>	<u>•</u>
Rear Ventilation Windows	•	•	•
Power Door and Tailgate Locks	•	•	•
Cruise Control	•	•	•
Steering Wheel-Mounted Audio Controls		•	•
Adjustable Steering Column	•	•	•
Instrument Panel-Mounted Shifter	•	•	•
Lower Instrument Panel Storage Compartment	•		
Driver's and Front Passenger's Vanity Mirrors		•	•
Sliding Sun Visor Extensions	•	•	•
Overhead Storage Compartment		•	•
Map Lights		•	•
Dome Light	•	•	•
Urethane-Coated Utility Floor	•	•	Cargo Area Only
Beverage Holders, Front and Rear	•	•	•
12-Volt Power Outlet	Front	Front/Rear	Front/Center Console/Rear
Door-Pocket Storage Bins, Rear with Bottle Holders	•	•	•
Driver- and Passenger-Side Seatback Pockets		•	•
Driver-Side Seatback Bungees, Front and Rear		•	
Rear Window Defroster	•	•	•
Rear-Seat Heater Ducts	•	•	
Cargo Area Tie-Down Anchors (4)	•	•	•
Cargo Area Storage Bins	•	•	•
Cargo Area Hooks (2)	•	•	•
Cargo Area Light	•	•	•
Floor Mats and Carpeted Floor (1st and 2nd row)			•
Center Console			•
INSTRUMENTATION			
Backlit Gauges	Blue	Blue	Copper
Tachometer	•	•	•
Digital Odometer and Digital Trip Meters (2)	•	•	•
Tire Pressure Monitoring System (TPMS) Indicator	•	•	•
Maintenance Minder™ System	•	•	•
Tailgate-Open Indicator	•	•	•
Fuel and Coolant Temperature Indicators	•	•	•
Low-Fuel Indicator	•	•	•

Low-Oil Pressure Indicator
Fuel Cap Indicator