

INTERNATIONAL®



908 C

Vehicle illustrated may include Optional Equipment and does not necessarily include all standard equipment.

RATINGS

MAXIMUM GROSS VEHICLE WEIGHT.....4,000 lbs.

STANDARD EQUIPMENT

AXLE, FRONT

FA-1 2,500-lb capacity
Heat-treated forged-steel I beam

AXLE, REAR

RA-18 3,500-lb capacity
Hypoid single reduction, 8½" ring gear
Semi-floating induction-hardened flanged shafts

Ratios: 3.31, 3.54 or 3.73

BODY

6 ft. 8 in. regular or Bonus-Load pick-up
with inner body tire carrier

BRAKE, PARKING

Mechanical control of rear service brakes
Foot pedal applied, finger lever released
Total lining area: 81.9 sq. inches

BRAKES, SERVICE

Self-adjusting hydraulic, dual operation
with warning light
Single-cylinder, single-piston front,
single-cylinder, double-piston rear
Size: 12 × 2" front, 11 × 1¾" rear
Total area: 179.7 sq. inches

CAB

All steel with safety glass windows
and sweep-around windshield
Door locks both sides with safety latches
Non-glare padded instrument panel with
ammeter, fuel, water temperature and oil
pressure gauges
Full-width adjustable seat with Torflex
spring construction, vinyl upholstery
and polyurethane foam cushion
Acoustical roof headliner

CAB (Continued)

Rubber floor mat with sound deadening
insulation; seat belts and shoulder
harness anchors
Fresh air heater and defroster
Padded sun visor for driver
Ash tray; hand choke
Two-speed non-glare electric windshield
wipers and electric washers
Chrome door mounted and inside rear
view mirrors

CLUTCH

10-inch 9-spring, single-plate
Hydraulic control; vibration dampener

COOLING SYSTEM

20-quart system capacity
Radiator frontal area: 497 sq. inches
Permanent type anti-freeze—20°F

ELECTRICAL SYSTEM

12-volt 32-amp alternator
50 amp-hr, 54 plate battery
Fuse panel in glove compartment
Dual stop and tail lights
Dome light; single electric horn
Directional signals: front in parking
lights, rear in stop lights
Traffic hazard switch
Back-up lights
Front side marker lamps

ENGINE

International V-266 gasoline, V-8
Gross BHP: 154.8 @ 4400 rpm
Gross torque: 227.1 lb/ft @ 2800 rpm
266 cu. in. displmt; 8.4 comp ratio

ENGINE (Continued)

Dry-type air cleaner; full-flow oil filter
Exhaust emission control

FINISH

Chassis—black; bumper—white
Cab, body and wheels: choice of
any standard IH color

FRAME

Pressed steel channel main rails
6¹³/₁₆ × 2³¹/₃₂ × 0.135"
3.68 section modulus
Formed-channel front bumper

FUEL TANK

19-gallon, mounted under cab

STEERING

S-8 gear, with 17-inch steering wheel
and collapsible column

SUSPENSION

Semi-elliptic steel leaf springs
Front: 2½ × 46"; 2,310-lb capacity
Rear: 2½ × 52"; 2,210-lb capacity
Front and rear shock absorbers

TRANSMISSION

T-13 3-speed synchromesh, direct
Floor mounted gear shift lever
Ratios: 2.80, 1.85, 1.00; 4.53 rev.

WHEELS AND TIRES

Single front and rear, with spare
7.75 × 15, 4-PR tubeless tires
5-stud disc wheels, with 5.50 K rims
5½" bolt circles
Painted hub caps, front and rear

OPTIONAL EQUIPMENT

AXLE, REAR

RA-28 3,500-lb capacity single reduction
with Powr-Lok limited slip differential
Ratios: 3.31, 3.54 or 3.73

BRAKES

Vacuum power assist

CAB

Passenger side padded sun visor
Left or right side arm rest
Right side chrome mirror
Truck type outside mirrors
Glove compartment lock; tinted glass
Deluxe trim package

CAB (Continued)

Exterior trim package
Air conditioner
Front bucket seats with console

CLUTCH

11-inch 9-spring

COOLING SYSTEM

Increased capacity cooling

ELECTRICAL SYSTEM

12-volt 61-amp alternator
60 or 70 amp-hr battery
Cigar lighter;
Dual electric horns; radio

ENGINE

Hand throttle control; automatic choke

FRAME

Chrome front or rear bumper
White rear bumper

SUSPENSION

Progressive rear springs

TRANSMISSION

T-44 4-speed synchromesh, direct

WHEELS AND TIRES

8.15 × 15., 4-PR tubeless tires
Deluxe chrome hub caps, front and rear

